

Description

3.5-mil*, cast PVC, commercial grade, reflective film. Available in white, yellow, red, orange, green and blue.

Release Liner

89# PE-coated silicone paper

Adhesive

Solvent polyacrylate, permanent

Applications

This film is suitable for the manufacture of short- to medium-term, outdoor, economical reflective traffic, guidance, warning and information signs as well as reflective lettering, numbers and symbols. The sheeting meets the ASTM D4956 specification for Type I, Class 1 retroreflective sheeting.

Technical Data

Thickness* (without liner and adhesive)	5.3-mil*
Temperature Resistance	-58°F to +180°F (adhered to aluminum)
Adhesive power* (FINAT-TM 1 after 24h, stainless steel)	3.42 lb/in film tear
Shelf life**	2 years
Minimum Life Expectancy*** (based on accepted Application procedures on vertical surfaces)	4 years (unprinted)
Application Temperature	50° F
Available Lengths Available Widths	150' (50 yard) 15" punched, 24", 30", 48"
Recommended Laminates	ORAGUARD® Series 290F, 293
Print Compatibility	Solvent, UV Curable, Latex, Thermal & Screen Printing: ORALITE® 5018 Screen Printing Ink is recommended

* average ** in original packaging at 68°F and 50% relative humidity *** standard central European climate



ORAFOL Americas – GA
1100 Oracal Parkway
Black Creek, GA 31308
Phone: 888.672.2251

ORAFOL Americas – CT
120 Darling Drive
Avon, CT 06001
Phone: 800.654.7570

ORAFOL Canada
2831 Bristol Circle
Oakville, Ontario L6H 6X5
Phone: 888.727.3374

Product Data

		Minimum coefficient of retroreflection (R) cd/fc/ft ² (cd • lx ⁻¹ • m ⁻²)				Daytime Luminance Factor (Y%)	
Observation Angle		0.2°		0.5°			
Entrance Angle		-4°	30°	-4°	30°	Minimum	Maximum
white	010	70	30	30	15	27	---
yellow	020	50	22	25	13	15	45
orange	035	25	7	13	4	10	30
red	030	14	6	7.5	3	2.5	15
green	060	9	3.5	4.5	2.2	3	12
blue	050	4	1.7	2	0.8	1	10

Color Specification Limits (Daytime)*

	1		2		3		4	
	x	y	x	y	x	y	x	y
white 010	0.303	0.300	0.368	0.366	0.340	0.393	0.274	0.329
yellow 020	0.498	0.412	0.557	0.442	0.479	0.520	0.438	0.472
orange 035	0.558	0.352	0.636	0.364	0.570	0.429	0.506	0.404
red 030	0.648	0.351	0.735	0.265	0.629	0.281	0.565	0.346
green 060	0.026	0.399	0.166	0.364	0.286	0.446	0.207	0.771
blue 050	0.140	0.035	0.244	0.210	0.190	0.255	0.065	0.216

Color Specification Limits (Nighttime)*

	1		2		3		4	
	x	y	x	y	x	y	x	y
white 010	no requirement							
yellow 020	0.513	0.487	0.500	0.470	0.545	0.425	0.572	0.425
orange 035	0.595	0.405	0.565	0.405	0.613	0.355	0.643	0.355
red 030	0.650	0.348	0.620	0.348	0.712	0.255	0.735	0.265
green 060	0.007	0.570	0.200	0.500	0.322	0.590	0.193	0.782
blue 050	0.033	0.370	0.180	0.370	0.230	0.240	0.091	0.133

*The four pairs of chromaticity coordinates determine the acceptable color in terms of the CIE 1931 Standard Colorimetric System measured with CIE Standard Illuminant D₆₅.



ORAFOL Americas – GA
1100 Oracal Parkway
Black Creek, GA 31308
Phone: 888.672.2251

ORAFOL Americas – CT
120 Darling Drive
Avon, CT 06001
Phone: 800.654.7570

ORAFOL Canada
2831 Bristol Circle
Oakville, Ontario L6H 6X5
Phone: 888.727.3374

Note:

All ORALITE® products are manufactured within an ISO 9001:2008 controlled manufacturing environment and batch traceability is possible on the basis of the roll number.

IMPORTANT NOTICE

When using ORALITE® sheeting, please comply with relevant national specifications. ORAFOL recommends obtaining the current requirements from your local authority and ensure product conformance with such requirements. Please contact ORAFOL for further information.

All ORALITE® products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORALITE® products is based upon research which the Company believes to be reliable, although, such information does not constitute a warranty. Because of the variety of uses of ORALITE® products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

Surfaces to which the material will be applied must be thoroughly cleaned from dust, grease or any contamination which could affect the adhesion of the material. Freshly lacquered or painted surfaces should be allowed to dry for at least three weeks and to completely cure respectively. The compatibility of selected lacquers and paints should be tested by the user, prior to application of the material. The self-adhesive reflective material can only be used for dry application. The low tensile strength of the material can make the removability of the reflective film more difficult. Please review applicable application information published by ORAFOL.

No warranty is given for purposes other than those listed in the Technical Datasheet or which are not processed according to ORAFOL's processing and handling instructions. The durability of the signs will depend on a variety of factors, including but not limited to substrate selection and preparation, compliance with recommended application guidelines, geographic area, exposure conditions and maintenance of the product and finished sign. Sign failures caused by the substrate or improper surface preparations are not the responsibility of ORAFOL. Please refer to the full warranty document available at www.orafolamericas.com for detailed information.

WARNING – This product may expose you to chemicals which are known in the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to – P65Warnings.ca.gov

ORALITE® is a trademark of ORAFOL Europe GmbH.



ORAFOL Americas – GA
1100 Oracal Parkway
Black Creek, GA 31308
Phone: 888.672.2251

ORAFOL Americas – CT
120 Darling Drive
Avon, CT 06001
Phone: 800.654.7570

ORAFOL Canada
2831 Bristol Circle
Oakville, Ontario L6H 6X5
Phone: 888.727.3374