

**CODE:** EZLAM54

**NAME:** ARMUR PSL 3.2mil Sand Clear Permanent

## DESCRIPTION:

- 80um Optical clear monomeric PVC laminates
- Sand finish
- High clarity PVC enhances appearance of digital images.
- Up to 24months protection of graphics from abrasion and moisture.
- Suitable for use over all digital inks printed graphics Retards color fade caused by UV light.

## PROPERTY

| PARAMETER                     |                                  | VALUE                                            |
|-------------------------------|----------------------------------|--------------------------------------------------|
| Film                          | Material                         | Optical Clear PVC                                |
|                               | Thickness                        | 80 um                                            |
|                               | Finish                           | Sand                                             |
|                               | E Value %(MD/CD) ASTM882         | 190%/210%                                        |
|                               | Shrinkage/mm(MD/CD) FTM-14       | 0.25/0.18                                        |
| Glue                          | Type                             | Solvent clear acrylic glue                       |
|                               | Thickness                        | 20 um                                            |
|                               | Init Tac 20min peel (N/in) FTM-9 | 11N                                              |
|                               | Hold (9.8N/in <sup>2</sup> )     | ≥ 48hours                                        |
|                               | 180°Peel (N/in) FTM-1            | 13N                                              |
| Liner                         | Liner type                       | Kraft paper (Blue grids)                         |
|                               | Weight(Thickness)                | 120 gsm                                          |
| Available size                | Width                            | 0.914/1.07/1.27/1.37/1.52m (36"/42"/50"/54"/60") |
|                               | Length                           | 50m (55Yd)                                       |
| Shelf time (20oC x 50% R.H)   |                                  | 24 Months                                        |
| Applying temperature Range °C |                                  | -10 ~65°C                                        |
| Durability                    |                                  | Up to 2 years                                    |

## APPLICATION

| Indoor | Outdoor | UV | Vehicle Wrapping | Photo Graphic | Floor Graphic |
|--------|---------|----|------------------|---------------|---------------|
| Y      | Y       |    |                  |               |               |

NOTE: All values shown are for reference only. The mentioned data are average of test results and should not be used for the purpose of lawsuit or warranty.

**Distributed by :**

**Médiatech** | (450) 622-6066 | Toll Free: (866) 622-6066 | [info@mediatech.ca](mailto:info@mediatech.ca) | [mediatech.ca](http://mediatech.ca)