HP Latex 800 Printer

Grow with high-value jobs and high-productivity printing—and sharpen your sustainability edge





Win the high-value jobs you are after

- Deliver vivid colors at high speed and get striking contrast using pure blacks.
- Expect reliable, sharp 4-point text with HP Latex printheads featuring 10-picoliter ink drops.
- Choose from a wide application range covering banners/textiles/poster paper, canvas, wallpaper, and vinyl.

Robust, smart, and productive printing

- Drive high productivity with saturated color at speeds up to 36 m²/hr outdoor¹, easy spindle-less loading.
- Control print operations virtually anytime, anywhere with HP PrintOS tools, and grow with HP Learn trainings.
- Work fast processing reprints and multi-copy jobs with a smart front panel, and store up to 100 jobs.
- Help reduce running costs with cost-effective 3liter HP ink cartridges, changed while the printer runs

Sharpen your sustainability edge with HP Latex

- Innovative water-based HP Latex Inks—no HAPs², no required hazard warning labels, and odorless prints.³
- Local HP Eco-Carton outer carton recycling.⁴
- Choose from a wide range of compatible ecoconscious media.5
- HP Latex prints are recyclable, returnable, or non-. hazardous and safe for disposal.⁶

For more information, please visit http://www.hp.com/go/latex800series

Join the community, find tools, and talk to experts. Visit the HP Latex Knowledge Center at https://hplatexknowledgecenter.com/

Dynamic security enabled printer. Only intended to be used with cartridges using an HP original chip. Cartridges using a non-HP chip may not work, and those that work today may not work in the future. More at: http://www.hp.com/go/learnaboutsupplies

¹ Outdoor mode (Banner) 4-pass, 100%. Based on internal HP testing in September 2020 on Avery 3001. Print speed may vary due to the adaptive printing mechanism to avoid image quality defects.
2 HP Latex Inks were tested for Hazardous Air Pollutants, as defined in the Clean Air Act, per U.S. Environmental Protection Agency Method 311 (testing conducted in 2013) and none were detected.
3 There is a broad set of media with very different odor profiles. Some of the media can affect the odor performance of the final print.
4 The is in k cartridge outer cartion is 100% recyclable through local cardboard/paper programs.
5 See http://www.hp.com/go/mwtw.hp.com/go/mw

Technical specifications Print

Print		
Printing modes	122 m²/hr - Max Speed (1-pass) 36 m²/hr - High Speed (4-pass) 25 m²/hr - Production Fast (6-pass) 20 m²/hr - Production Quality, Textiles and Backlits (8-pass) 17 m²/hr - High Saturation (12-pass) 14 m²/hr - High Saturation Backlits and Textiles (14-pass) ¹	
Print resolution	Up to 1200 x 1200 dpi	
Ink types	Water-based HP Latex Inks	
Ink cartridges	8 (black, cyan, light cyan, light magenta, magenta, yellow, HP Latex Optimizer, HP Overcoat)	
Cartridge size	3L	
Printheads	8 (2 cyan/black, 2 magenta/yellow, 2 light cyan/light magenta, 1 HP Latex Optimizer, 1 HP Overcoat)	
Long-term print-to-print repeatability	95% of colors $\leq 1.5 \text{ dE2000}^2$	
Media		
Handling	Roll feed, take-up reel, wiper roller ³ , automatic horizontal cutter (for vinyl, banner and canvas ⁴ , paper-based media, and film)	
Media types	Banners, self-adhesive vinyls, films, fabrics, papers, wall coverings, canvas, synthetics, mesh, textiles ⁵	
Roll size	254 to 1625-mm rolls (580 to 1625-mm rolls with full support)	
Roll weight	55 kg	
Roll diameter	250 mm	
Thickness	Up to 0.5 mm	
Applications	Banners; Displays; Exhibition and event graphics; Exterior signage; Indoor posters; Interior decoration; Light boxes - firm; Light boxes - paper; Murals; POP/POS; Posters; Textile; Vehicle graphics; Window graphics; Sitckers	
Connectivity		
Interfaces	Gigabit Ethernet (1000Base-T)	
Dimensions (w x d	x h)	
Printer	2583 x 866 x 1402 mm	
Shipping	2753 x 1100 x 1666 mm	
Operating area	2793 x 2100 mm	
Weight		
Printer	292 kg	
Shipping	430 kg	
What's in the box	HP Latex 800 Printer, printheads, maintenance cartridge, printer stand, take-up reel, user maintenance kit, edge holders, quick reference guide, setup poster, documentation software, power cords, air purgers, 2-in spinle adaptor	
Environmental ran	ges	
Operating temperature	15 to 30°C	
Operating humidity	20 to 80% RH (non-condensing)	
Acoustics		
Sound pressure	60 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep)	
Sound power	7.8 B(A) (operating), 5.5 B(A) (idle), <3.5 B(A) (sleep)	
Power		
Consumption	1.8-2.8 kW (5 kW peak) (printing), 105 W (ready)	
Requirements	Input voltage (auto ranging) 200-240 V two wires and PE; S0/60 Hz (\pm 3 Hz); two power cords; 16 A max per power cord	
Certification		
Safety	IEC 60950-1+A1+A2 compliant; IEC 62368-1 compliant; USA and Canada (CSA listed); EU (LVD, EN 60950-1 and EN 62368-1 compliant); Russia, Belarus, and Kazakhstan (EAC); China (CCC)	
Electromagnetic	Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia and New Zealand (RCM), Japan (VCCI), Korea (KCC), China (CCC)	
Environmental	ENERGY STAR®; RoHS (WEEE, EU, EAEU, China, Korea, India, Ukraine, Turkey); REACH; EPEAT Silver; OSHA; (E marking compliant; Meets AgBB criteria; French VOC A+; Greenguard Gold; UL Ecologo; ZDHC - Level 1	
Warranty	One-year limited hardware warranty	

Ordering information

Product		
YOU21A	HP Latex 800 Printer	
Accessories		
21V10A 7HR16A 7HR18A 7HR19A T7U73A	HP Latex 700/800 User Maintenance Kit HP Latex 700/800 Textile Kit Accessory HP Latex 700/800 ink Collector Foams Kit HP Latex 700/800 Media Loading Accessory HP Latex 500/700/800 Wiper Roller	
Original HP printing supplies		
4UU94A 4UU96A 4UV84A 4UV85A	HP 836 Optimizer Latex Printhead HP 836 Latex Maintenance Cartridge HP 873 3-liter Black Latex Ink Cartridge HP 873 3-liter Cyan Latex Ink Cartridge	

1UV86A	HP 873 3-liter Magenta Latex Ink Cartridge
1UV87A	HP 873 3-liter Yellow Latex Ink Cartridge
1UV88A	HP 873 3-liter Light Cyan Latex Ink Cartridge
1UV89A	HP 873 3-liter Light Magenta Latex Ink Cartridge
1UV90A	HP 873 3-liter Optimizer Latex Ink Cartridge
1UV91A	HP 873 3-liter Optimizer Latex Ink Cartridge
1UV95A	HP 836 Black/Cyan Latex Printhead
1UV95A	HP 836 Magenta/Yellow Latex Printhead

Original HP large format printing materials

HP PVC-free Wallpaper (UL GREENGUARD GOLD Certified⁶, FSC® certified⁷, meets AgBB criteria⁸) HP Photo-realistic Poster Paper HP Premium Satin Canvas HP Prime Mate Air GP (REACH compliant⁹) HP Premium Removable Gloss Adhesive Vinyl (REACH compliant⁹)

For the entire HP Large Format Printing Materials portfolio, please see HPLFMedia.com.

Service and Support

U13DBE HP 2 year Next Business Day with Defective Media Retention U13DDE HP 3 year Next Business Day with Defective Media Retention U13DLPE HP 1 year Post Warranty Next Business Day with Defective Media Retention U13DRPE HP 2 year Post Warranty Next Business Day with Defective Media Retention

ECO highlights

- Inks do not use reactive monomer chemistry, are ozone-free, and meet the ZDHC standard¹ Can win new business with odorless prints, UL ECOLOGO®/UL GREENGUARD Gold Certified ink, and more² High-volume 3-liter HP Eco-Carton ink cartridges—carton-based design significantly reduces plastic :

Please recycle printing hardware and eligible printing supplies and prints. Find out how at our website: http://www.hp.com/ecosolutions

¹ See http://www.roadmaptozero.com. Printing with HP Latex Inks avoids the problematic reactive monomers associated with UV printing. Acrylate monomers present in uncured UV inks and UV-gel inks can damage skin. ² There is a broad set of media with very different odor profiles. Some of the media can affect the odor performance of the final print. For certifications, see http://www.ul.com/EL and http://www.ul.com/gg.

Print speeds may vary due to the adaptive printing mechanism to avoid image quality defects.
 The color variation between printed jobs has been measured at 12 pass mode on vinyl media following best practices for tiling layouts and within this limit: 95th percentile of pairwise color differences (95% of colors) 1 d. 42000. Reflective measurements on a 943 color target under CE standard lluminant DS, and according to the standard CIbeD2000 as per CIB Oraft Standard DS 014-6/E 2012. 5% of colors) and according to the standard CIbeD2000 as per CIB Oraft Standard DS 014-6/E 2012. 5% of colors may experience variations above 1 dE2000. Backlit substrates
 ⁴ Wiper roller is an optional accessory.
 ⁴ Automatic horizontal cutter is for use with thinner banners and canvas only. It is recommended to perform a test.
 ⁵ Textile RK Accessory required for long runs of textile and porous textile.
 ⁶ LIGREENGUARD GOLD Certification to UL 2818 demonstrates that products are certified to ULS GREENGUARD standards for low chemical emissions into indoor air during product usage. For more information, visit http://www.ul.com/gg or http://www.greenguard.org.
 ⁷ Trademark license code FSC-(115319).
 ⁸ With HP Latex Inks, prints meet AgBB criteria for health-related evaluation of VOC emissions. See http://unweltbundesamt.de/en/topics/health/commissions.working-groups/committee-for-health-related-evaluation-of-building.
 ⁹ This product does not contain substances listed as SVHC (155) per Annex XIV of the EU REACH directive published as of June 16, 2014 in concentrations exceeding 0.1%. To determine the status of SVHC in HP products, see the HP REACH Declaration published at HP Printing Products and Consumable Supplies.



