

Introduction

ORAFOL Americas Inc. recommends that you maintain ORAGUARD 2815+ paint protection films with to maximize the film's appearance and health for its entire lifespan.

Washing ORAGUARD 2815+

- Vehicle should not be washed for minimum 72 hours after install.
- Hand washing is the recommended way to clean ORAGUARD 2815+. Automatic car washes potentially can cause damage to the film, with the likelihood of surface scratches penetrating the topcoat.
- Wash with pH-neutral soaps and solutions, keep away from harsh chemicals and abrasive materials.
- Avoid using pressure washers with high-pressure, staying away from all edges as it will be at risk of lifting and/or become damaged.
- Assume 2815+ products are ceramic coated and use ceramic friendly products.
- 2815+ films with our hydrophobic topcoat may interfere with the application of other coatings.

Products to Avoid

- Clay bars can clean the surface of film but can damage the topcoat and potentially discolor the film, use with caution.
- Waxing compounds and oil-based waxes or pomades should not be used.
- Do not use pigmented waxes or waxes containing naphtha or kerosene.
- Using any polishers or buffers can create too much heat and friction, damaging the adhesive.

Repairing ORAGUARD 2815+

Surface scratches in the film can be repaired with some soft heat. Recommended using warm water or heat gun at low speed to the affected area (note: if the scratch has penetrated through the topcoat, the scratch will not go away).

ORAFOL + Koch-Chemie

Koch-Chemie products have been tested to show optimal results with ORAGUARD Paint Protection Films and are the recommended brand of products to use when caring for the film.

Highlighted Shampoos

- Gentle Snow Foam (Gsf) – pH neutral cleaning foam that will not corrode the hydrophobic topcoat
- Ceramic Effect Shampoo (Ces) – cleans and seals surfaces in one step
- NanoMagic Shampoo (Nms) – long lasting protective and water-repellent nano-layer

Highlighted Protection

- Ceramic Body (Cb0.01) – thin protective layer creating a lotus effect behavior with easy to clean properties; up to 5 years
- Spray Sealant (S0.02) – quick and easy sealant spray for high-gloss surface; up to 6 months
- Hydro Foam Sealant (S0.03) – premium wet sealant for hydrophobic surface; up to 3 months

Note: Any other aftermarket products should be tested before applying to ORAGUARD at the installers' own risk



ORAFOL Americas - GA

1100 Oracal Parkway
Black Creek, GA 31308

912-851-5000 • Fax | 912-851-5110
Toll Free | 888-672-2251

ORAFOL Americas - CT

120 Darling Drive
Avon, CT 06001

860-676-7100 • Fax | 860-676-7199
Toll Free | 800-654-7570

ORAFOL Canada

2831 Bristol Circle
Oakville, Ontario L6H 6X5

905-829-2828 • Fax | 905-829-9941
Toll Free | 888-727-3374