



VESCOM TABBY 20 OZ NON WOVEN

Vescom Tabby delivers colorful, high-definition wall art with high-end results. Certified for HP Latex Inks, this commercial grade media also meets Environmental Protection Agency (EPA) requirements for low-VOC emitting products and is Class A fire resistant.

With the look and feel of fine linen embossing, Vescom Tabby delivers colorful, high-definition wall art with high-end results. Certified for HP Latex Inks, this commercial grade media also meets Environmental Protection Agency (EPA) requirements for low-VOC emitting products and is Class A fire resistant.

A Type II Compliant, commercial grade wallcovering, Vescom Tabby is durable enough for commercial environments subject to wear and tear, while at the same time is environmentally safe for sensitive spaces like schools, hospitals and public buildings. Compatible with Latex, Eco-solvent, Solvent and UV inks, this phthalate- and formaldehyde-free substrate installs easily with common adhesives and installation techniques.

Benefits	Applications	Customers
- Type II PVC - Commercial Grade, Class A Fire Rating - Meets EPA requirements for low VOC emitting products - Phthalate-free substrate - Compatible with all Latex, Eco-Solvent, Solvent, and UV Inks - Certified for HP Latex Inks	- Corporate environment murals - Healthcare facilities - Schools - Retail and entertainment venues	- Large-format print service - Design firm/ad agency - In-house - Federal government - Schools - Sign companies



Roll Size(s)	TABNW54150: 54 in x 150 ft, TABNW54300: 54 in x 300 ft
Material Type	100% PVC face
Texture	Soft Linen
Backing	Non Woven Backing
Gauge	18 mil
GSM	448
Weight	20 oz linear yard
Opacity	100%
Whiteness	89.44
Brightness	87.10
Finish	Liquid top coatings can be used for added protection or desired finishes. To achieve Type II results, product must be paired with Marabu ClearShield Wall Armor.
Gloss Level	6.4 (60)
RIP & Printer Media Settings	For the best and most consistent results, a profile should be created using an external color calibrator in conjunction with your RIP and color matching software. If a custom profile is not available, the on-board media setting, Cast Vinyls, typically used for vehicle wraps, is a good place to start. Optimal printer settings will vary from printer manufacturers. A suggested starting point is setting the pre- and post-heaters to 122° F (50° C).
Light Fastness	Contact the ink manufacturer for light-fastness data. The fading time of inkjet ink is a direct result of the inks that you choose to use and the environment where the print is displayed.
L*	94.33
A*	-0.18
B*	-0.62
Fire Rating	Class A
Core Size	3 in ID core
Optimal Service Environment	For end use: -40° to 176° F (-40°-80° C), For printing: 60° to 80° F, 50% RH relative humidity.
Ideal Storage Conditions	70° F (21° C), 50% RH (a controlled environment is recommended), store vertically in original packaging
Color	Bright white PVC
Ink Compatibility	Latex, Low-solvent, Solvent, UV-curable
Shelf Life	1 year storage in original package under recommended storage conditions above.



Médiattech
Papier d'impression numérique grand format